

700mW 16-Channel 1.2 GHz Wireless Video Transmitter-Receiver & 700mW 12-Channel 2.4 GHz Wireless Video Transmitter-Receiver



Transmitter Specifications (blue unit):

- Dimensions: 65 x 45 x 18 mm
- Input: 12V regulated at 210mA
- Output: 700mW or 28.5 dB
- Frequency: 0.9-1.3 or 2.29-2.51 GHz
- Channels: 16/12 channels 0-9, A-F
- Temperature: -20C to +60C
- Contents: 1 x Transmitter,
1 x Receiver
2 x 120/240V to 12V/1A
2 x Connecting cables

Receiver Specifications (grey unit):

- Dimensions: 105 x 75 x 20 mm
- Input: 12V regulated power
- Frequency: 0.9-1.3 or 2.29-2.51 GHz
- Channels: 16/12 channels 0-9, A-F

Operating Requirements:

- To prevent electrical shock, do not touch the transmitter antenna and avoid water
- Use only the supplied regulated power supplies and disconnect when not in use
- Do not disassemble either unit without written permission

Connections:

- Connect the short video/power cable to the transmitter using the 3-way plug
- Then connect the yellow plug of this cable to the video output of the camera
- Also connect the 12V male power plug to the camera
- Plug the 12V supply into the female socket to power both camera and transmitter
- The white audio plug is not normally used
- Plug the second 12V supply into the receiver
- Plug the video output of the receiver into a composite video display or computer

Operating Instructions:

- Push the small black button on the transmitter to cycle through the channels
- Push the small black button on the receiver to select the same channel number
- The selected channel number will be remembered when the unit is powered up